




Wireport™ Plates

The Wireport™ plate eliminates the need for plate connectors and provides a clean professional appearance to your custom installation. They are designed to mount directly to standard low voltage mounting brackets and backless boxes. By eliminating the connectors at the wall, the installer reduces labor and material costs and improves signal integrity thereby making your installations more competitive and reliable. Wireport™ plates are perfect for both wall and ceiling installations for audio, video, security, and office networking.

They are sold individually or in master packs of 25 and are available in industry standard colors of White, Almond, Ivory, Brown, and Black.



	Part No.	Description	Hole Size (Diameter)	Hole Area (Sq. In.)
	1-Gang Wireport™			
	1GWH	1-gang White Wireport™ Plate, w/screw hardware	1.56"	1.92"
	1GAL	1-gang Almond Wireport™ Plate, w/screw hardware	1.56"	1.92"
	1GIV	1-gang Ivory Wireport™ Plate, w/screw hardware	1.56"	1.92"
	1GBR	1-gang Brown Wireport™ Plate, w/screw hardware	1.56"	1.92"
	1GBK	1-gang Black Wireport™ Plate, w/screw hardware	1.56"	1.92"
	2-Gang Wireport™			
	2GWH	2-gang White Wireport™ Plate, w/screw hardware	1.8"	2.54"
	2GAL	2-gang Almond Wireport™ Plate, w/screw hardware	1.8"	2.54"
	2GIV	2-gang Ivory Wireport™ Plate, w/screw hardware	1.8"	2.54"
	2GBR	2-gang Brown Wireport™ Plate, w/screw hardware	1.8"	2.54"
	2GBK	2-gang Black Wireport™ Plate, w/screw hardware	1.8"	2.54"
	Décor-Style Wireport™			
	DC1WH	White Décor-Style Wireport™ Plate, w/screw hardware	.670 x 1.56	.900
	DC1AL	Almond Décor-Style Wireport™ Plate, w/screw hardware	.670 x 1.56	.900
	DC1IV	Ivory Décor-Style Wireport™ Plate, w/screw hardware	.670 x 1.56	.900
	DC1BK	Black Décor-Style Wireport™ Plate, w/screw hardware	.670 x 1.56	.900



White



Almond



Ivory



Brown



Black

Wireport™ is a Trademark of MIDLITE®



Member

www.midlite.com

Warehouse: 115 Wordell Street, Fall River, MA 02721

Office Mail: PO Box 70189, No. Dartmouth, MA 02747

tel 508.676.5169 / toll free 800.606.5169 / fax 508.861.0105

